



# PERFORMANCE BULLETIN

Product     Application     Service     General    news from

September 4, 2000



## The Newest Line of Fleck® Control Valves To Meet Your Application Needs

### Commercial

#### 2930



#### Superior Performance

C<sub>v</sub> 25.8 Yields Service Flow of 100 gpm  
C<sub>v</sub> 18.1 Yields Backwash Flow of 90 gpm

Dual Piston Control ... Ideal for Multiple Tank Systems

Top Mount  
Side Mount will be available in November 2000

#### 3130



#### Superior Value

C<sub>v</sub> 24.2 Yields Service Flow of 93 gpm  
C<sub>v</sub> 21.4 Yields Backwash Flow of 107 gpm

Regenerates Up To 20 ft<sup>3</sup> of Resin

Top Mount  
Side Mount will be available in November 2000



## Residential

### 4650



#### **Hot Water Capability**

Combines Rugged, Lead-Free Brass Body  
With Time-Tested “L” –Style Powerhead

Used With 5600-Style Yokes and ByPasses

### ProFloSE



#### **Dependable Performance**

C<sub>v</sub> Yields:      Service Flow of 21 gpm  
                         Backwash Flow of 17 gpm

Reliable, Clutch-Free Electronic Powerhead

Professional Program Valve

As always, thank you for using Fleck controls.

Sincerely,  
Pentair Water Treatment, Inc.

Jay Runkle  
Technical Product Support