



PERFORMANCE BULLETIN

Product Application Service General news from



January 24, 2003

New High Flow Distributors in 1.05" and 32mm

The new high-flow distributors are now available for order in both 1.05" and 32mm sizes. The new design provides a high-performance, durable construction using NSF approved materials. These new distributors are for cold water applications only, up to 110°. The new high flow distributors will not be available as a valve configuration, but will be sold as line items (parts) only with no tube.

Top View



Side View



Bottom View



Part numbers and technical data listed below.

Part No.	Description	Slot Width (in.)	Total Slots	Flow Rate @15 psi drop (Distributor Only)	Cv (Distributor Only)
High-Flow Distributor Assemblies					
40922	Distributor, 1.05"	0.008/0.010	326	110 GPM	26.6
40924	Distributor, 32mm	0.008/0.010	326	110 GPM	26.6
Fleck Distributor Assemblies					
13851	Distributor, 1", Gray, Standard	0.010/0.012	90	64 GPM	16.4
13851-01	Distributor, 1", White, Wide	0.019/0.022	90	84 GPM	21.7
13851-02	Distributor, 1", Red, Narrow	0.007/0.009	90	51 GPM	13.3

As always, thank you for using Fleck controls.

Sincerely,

Pentair Water Treatment, Inc.

Wayne Pløense
Technical Sales/Support