

K52 SERIES DIAPHRAGM VALVE MASTER CHART

* FILL IN PROPER DESIGNATIONS TO DETERMINE PRODUCT NUMBER: **K 5 2 - X 2 - 4**

BODY SIZE
0 = 1/2"
1 = 1"
4 = 1-1/2"
6 = 2-1/2"

END CONNECTIONS (X std)
X = None

BODY & CAP MATERIAL (2 std)
2 = Noryl

VALVE OPTIONS (00 std for K521, K524, K526; 01 std for K520) [opt 00, 12, 32, & 42 not valid on K520]		
[NC & XNC not valid with solenoid options]		
00 = NO	12 = NO, LS, SAC	42 = NC, LS, SAC
01 = NO, SAO	21 = NO, PI, SAO	B2 = XNC, SAC
02 = NO, SAC	30 = NC	SX = Special Valve **
10 = NO, LS	31 = NC, SAO	
11 = NO, LS, SAO	32 = NC, SAC (See note 1)	

SEAL MATERIALS (1 std) (Option no. 2 not available on series 526 valves)					
OPT.	OPERATING DIAPHRAGM	SEALING DISK	DYNAMIC SEALS	STATIC SEALS	KIT SERIES
1	Buna-N	EP	EP	EP	RA
2	Fluoroelast.	Fluoroelast.	Fluoroelast.	Fluoroelast.	RAVfV
5	Buna-N	Fluoroelast.	Fluoroelast.	Fluoroelast.	RAV
6	Buna-N	Butyl	Butyl	Butyl	RAJ

INTERNAL PARTS (4 std)
4 = Noryl/PVC (140°F (60°C) Valve Rating)

DRILL & TAP BOSSES (0 std [1/8" NPT std for K520/K521/K524; 1/4" NPT std for K526])		
0 = None	3 = Boss #3	6 = Bosses #1,2
1 = Boss #1	4 = Boss #4	7 = Bosses #1,3
2 = Boss #2	5 = Bosses #1,2,3,4	

SOLENOID OPTIONS (0 std) [Solenoid option not available with NC or XNC valves]		
0 = None	2 = Energize to Close (EC)	4 = EO w/ Dry Drain
1 = Energize to Open (EO)	3 = Independent pressure (IP)	5 = EC w/ Dry Drain

SOLENOID FEATURES (0 std)	
0 = None	E = 220V/50HZ, NEMA 4
D = 115V/60HZ, NEMA 4	F = 24V/60HZ, NEMA 4

* To create a valve number replace each "_" with the proper number or letter for the feature you desire. For example, a 2" Plastic Valve Model K524 with Normally Closed and Spring Assist Closed Options is designated as a K524-X232-14000.

** A special valve will have a custom drawing number (_ - - - - -) and the item number format is (K52?-?2SX- - - - -) where the last 5 numbers (Far Right) are the last five digits of the drawing number.

Valve Option Notes:

- Option 32 (NC, SAC) not possible on K520, use option B2 (XNC, SAC).

REV.	ECO NO.	DESCRIPTION	BY/DATE
E	21190	Revised for Pentair ECN release	JJJ 17-Nov-09

BR42983